

Type LTGE - general purpose, CE Certified Liquid-tight flexible metallic conduit

General Purpose, CE compliant Liquid-tight Flexible Metallic Conduits provide excellent strength and liquid-tight performance

Features & Benefits:

- Designed to meet UL 360 ID/OD dimension requirements
- Full compliance to IEC 61386 requirements, CE compliant
- Trade sizes from 3/8 to 6" (12mm to 155mm)
- Coordinated performance with Series 52/53 Steel Fittings
- Ingress protection ratings aligned with industrial enclosures
- Smooth extruded jackets provide best performance with fittings

Applications:

- General Purpose specification grade liquid-tight flexible metallic conduit
- Used extensively in the machine tool and other industrial environments where flexibility is necessary for motion, vibration and bending
- The inherent sunlight resistance of PVC enables this product to be used in outdoor applications
- Liquid-tight applications against water, oils, cutting fluids, mild acids
- For use in electrical circuits up to 1,000 V

Construction / Material / Finish:

- Hot-dipped Zinc Galvanized Steel Core
- PVC (Polyvinyl Chloride) extruded smooth jacket
- Ink jet printed ratings and technical information
- Full range of trade sizes from 3/8 to 6" (12 to 155mm)
3/8 to 2", square lock design with cord filler
2-1/2" to 6", fully interlocked design
- Colors: Machine tool gray standard, black optional

Environment ratings:

Working Temperature:

- Gen:
 - Dry: -20 to +80°C (-4 to +176°F)
 - Oil: -20 to +70°C (-4 to +158°F)
 - Wet: -20 to +60°C (-4 to +140°F)
- IEC/CE:
 - Gen: -15 to +60°C (+5 to +140°F)

Chemical resistance guide:

- See publication TDS000117

T&B Liquidtight Systems™



Certifications / Standards:



Conforms to:

- IEC 61386-1, -23, Conduit Systems for Cable Management
EU Doc: EC-012-16-160
- JIC Mass Production Equipment (Joint Industrial Council)
- RoHS (Restriction of Hazardous Substance Directive)

Standards requirements:

Designed to UL 360 and CSA C22.2 No. 56 standard requirements including:

- ID and OD Dimensions

Meets all IEC 61386-1, -23 standard requirements including:

- Compression strength - Code 4 Heavy; 1250 N/50mm
- Impact strength - Code 4 Heavy; 6 Joules
- Tensile strength - Code 3 Medium; 500 N/2 min.

Ingress protection:

- Provides "Ingress Integrity" between enclosures, fittings, conduits & seals when using LTGE Conduits and Series 5200/5300 Liquidtight Fittings
- Covers all trade sizes from 3/8" to 4" (12 .. 103mm)

System ingress ratings:

- Products tested and comply with UL 50/50E and CSA C22.2 No. 94 Type Rating requirements
 - Indoor: Type 4, 12, 13
 - Outdoor: Type 3, 3R, 4
- NEMA 250: Type 3, 3R, 4, 12, 13

IEC system ingress rating:

- IP ingress protection per IEC 60529 requirements
- IEC ingress rating: IP66, IP67






Type LTGE - general purpose, CE Certified

Product selection and dimensions

Product selection

Trade size			Coil length										Weight	
UL	CSA	ISO BS EN	Carton		Standard reel				Bulk reel				lbs/ft	kg/m
Inches	mm	mm	Part No./GID	Feet	Meter	Part No./GID	Feet	Meter	Part No./GID	Feet	Meter			
3/8	12	16	LTGES01G-C	100	30	LTGES01G-K	500	150	LTGES01G-L	1,000	300	0.20	0.30	
			7TAA012LSOR0000			7TAA012LSOR0024			7TAA012LSOR0044					
1/2	16	20	LTGES02G-C	100	30	LTGES02G-K	500	150	LTGES02G-L	1,000	300	0.24	0.36	
			7TAA012LSOR0001			7TAA012LSOR0025			7TAA012LSOR0045					
3/4	21	25	LTGES03G-C	100	30	LTGES03G-K	500	150	LTGES03G-L	1,000	300	0.33	0.49	
			7TAA012LSOR0002			7TAA012LSOR0026			7TAA012LSOR0046					
1	27	32	LTGES04G-C	100	30	LTGES04G-J	400	120	—	—	—	0.53	0.79	
			7TAA012LSOR0003			7TAA012LSOR0027								
1-1/4	35	40	LTGES05G-B	50	15	LTGES05G-E	200	60	—	—	—	0.68	1.01	
			7TAA012LSOR0004			7TAA012LSOR0028								
1-1/2	41	50	LTGES06G-B	50	15	LTGES06G-D	150	45	—	—	—	0.88	1.31	
			7TAA012LSOR0005			7TAA012LSOR0029								
2	53	63	LTGES07G-B	50	15	LTGES07G-C	100	30	—	—	—	1.02	1.52	
			7TAA012LSOR0006			7TAA012LSOR0030								
2-1/2	63	70	LTGES08G-A	25	8	LTGES08G-G	275	80	—	—	—	1.92	2.86	
			7TAA012LSOR0007			7TAA012LSOR0031								
3	78	80	LTGES09G-A	25	8	LTGES09G-P	175	50	—	—	—	2.52	3.75	
			7TAA012LSOR0008			7TAA012LSOR0032								
4	103	100	LTGES11G-A	25	8	LTGES11G-C	100	30	—	—	—	3.50	5.21	
			7TAA012LSOR0009			7TAA012LSOR0033								
5	129	—	LTGES12G-A	25	8	—	—	—	—	—	—	4.68	6.96	
			7TAA012LSOR0010			—	—	—	—	—	—			
6	155	—	LTGES13G-A	25	8	—	—	—	—	—	—	5.72	8.51	
			7TAA012LSOR0011			—	—	—	—	—	—			



Dimensions

Part number	Trade size			Minimum inside bend radius				Inches				Millimeters			
	UL	CSA	ISO BS EN	Static		Dynamic		Inside (ID)		Outside (OD)		Inside (ID)		Outside (OD)	
				Inches	mm	Inches	mm	Min	Max	Min	Max	Min	Max	Min	Max
LTGES01G-*	3/8	12	16	1.5	38	4.0	102	0.484	0.504	0.690	0.710	12.3	12.8	17.5	18.0
LTGES02G-*	1/2	16	20	2.0	51	5.0	127	0.622	0.642	0.820	0.840	15.8	16.3	20.8	21.3
LTGES03G-*	3/4	21	25	2.5	64	6.0	152	0.820	0.840	1.030	1.050	20.8	21.3	26.2	26.7
LTGES04G-*	1	27	32	3.0	76	12.0	305	1.041	1.066	1.290	1.315	26.4	27.1	32.8	33.4
LTGES05G-*	1-1/4	35	40	3.5	89	15.0	381	1.380	1.410	1.630	1.660	35.1	35.8	41.4	42.2
LTGES06G-*	1-1/2	41	50	4.5	114	17.0	432	1.575	1.600	1.865	1.900	40.0	40.6	47.4	48.3
LTGES07G-*	2	53	63	5.5	140	22.0	559	2.020	2.045	2.340	2.375	51.3	51.9	59.4	60.3
LTGES08G-*	2-1/2	63	70	8.0	203	30.0	762	2.480	2.505	2.840	2.875	63.0	63.6	72.1	73.0
LTGES09G-*	3	78	80	10.0	254	36.0	914	3.070	3.100	3.460	3.500	78.0	78.7	87.9	88.8
LTGES11G-*	4	103	100	12.0	305	52.0	1,321	4.000	4.040	4.460	4.500	101.6	102.6	113.3	114.3
LTGES12G-*	5	129	—	17.5	445	—	—	4.975	5.035	5.505	5.565	126.4	127.9	139.8	141.4
LTGES13G-*	6	155	—	22.5	572	—	—	6.015	6.075	6.565	6.625	152.8	154.3	166.8	168.3

Note: Product must be installed in accordance with applicable national and local electrical codes.

Contact us

ABB Inc.
 Electrification Products
 8155 T&B Boulevard
 Memphis, TN 38125
www.abb.us/lowvoltage

© 2018 ABB Inc. All rights reserved.

2 of 2 Type LTGE | Technical data sheet | TDS000002 C

