EMT Adapters

NEC/CEC: Rated for Ordinary Locations

Applications

• Adaptors are used to connect non-threaded fittings to threaded fittings.

Features

- Malleable iron clamps are exceptionally rugged and strong.Steel adapters offer economy and have integral formed gussets for excellent strength.


Material/Finish

• Stee/zinc electroplated



TWAD-50

Illustrated Dimensions



Trade Size (Inches)	Dimensions in Millimeters (Inches)			Weight per 100	Catalog
	Α	В	C	kg (lb)	Number
No-Thread to Thread	ded Fittings – Convers	ion Adapters – Steel			
1/2	11.2 (0.44)	3.3 (0.13)	25.4 (1.00)	1.00 (2.20)	TWAD-50
3/4	12.7 (0.50)	3.3 (0.13)	36.6 (1.44)	1.81 (4.00)	TWAD-75
1	6.0 (0.63)	3.3 (0.13)	38.1 (1.50)	2.72 (6.00)	TWAD-100
1-1/4	19.1 (0.75)	4.8 (0.19)	50.8 (2.00)	4.99 (11.00)	TWAD-125
1-1/2	19.1 (0.75)	4.8 (0.19)	57.2 (2.25)	5.44 (12.00)	TWAD-150
2	19.1 (0.75)	6.4 (0.25)	71.4 (2.81)	8.62 (19.00)	TWAD-200

