

# Eaton 127700LR-ENT

Catalog Number: 127700LR-ENT

Eaton Cooper Power series disconnect switch, Vertical or underhung, 2.25" B.C. porcelain, 1010kV, Distribution, 15.5 kV, 600 A, Tin-plated 2-hole NEMA terminal pads, Galvanized steel hook, Special blade assembly (18" spacing) for Entergy

## General specifications



Photo is representative

Product Name	Catalog Number
Eaton Cooper Power series disconnect switch	127700LR-ENT
	UPC
	194006020367
Product Length/Depth	Product Height
30 in	9.75 in
Product Width	Product Weight
4.375 in	48.501 lb
Compliances	Certifications
Not Applicable	IEEE C37.34

## Accessories

### Special features

Special blade assembly (18" spacing) for Entergy

### Terminal options

Tin-plated 2-hole NEMA terminal pads

## Electrical Ratings

### Amperage Rating

600 A

### Basic impulse level full wave crest

1010kV

### Phase type

Single-phase

### Voltage rating

15.5 kV

## Application

### Application

Distribution

## Description

### Backstrap options

REA backstrap (4-3/8" x 9" bolts)

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

2.25" B.C. porcelain

### Switch type

Disconnect switch

## Loadbreak Hook

### Loadbreak hook material

Galvanized steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

### Specifications and datasheets

[Eaton Specification Sheet - 127700LR-ENT](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)