

Eaton 127701CL-OUC

Catalog Number: 127701CL-OUC

Eaton Cooper Power series disconnect switch, Vertical or underhung, 2.25" B.C. porcelain, 125 kV, Distribution, 25.8 kV, 600 A, Tin-plated 2-hole NEMA terminal pads, Galvanized steel hook

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Cooper Power series disconnect switch	127701CL-OUC
	UPC
	194006020626
Product Length/Depth	Product Height
30 in	9.75 in
Product Width	Product Weight
4.375 in	43.871 lb
Compliances	Certifications
Not Applicable	IEEE C37.34

Accessories

Terminal options

Tin-plated 2-hole NEMA terminal pads

Description

Backstrap options

15" x 2" backstrap with 6 3/4" slot spacing (2-3/8" x 9" bolts)

Blade stop options

90° blade stop, can be field-removed for 180° travel

Insulation material

2.25" B.C. porcelain

Switch type

Disconnect switch

Application

Application

Distribution

Electrical Ratings

Amperage Rating

600 A

Basic impulse level full wave crest

125 kV

Phase type

Single-phase

Voltage rating

25.8 kV

Loadbreak Hook

Loadbreak hook material

Galvanized steel hook

Mounting

Mounting configuration

Vertical or underhung

Resources

Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - 127701CL-OUC](#)