

# Eaton 127701CPS

Catalog Number: 127701CPS

Eaton Cooper Power series disconnect switch, Vertical or underhung, 2.25" B.C. porcelain, 125 kV, Distribution, 25.8 kV, 600 A, Tin-plated 2-hole NEMA terminal pads, Standard 15" backstrap (2-3/8" x 9" bolts)

## General specifications



Photo is representative

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Cooper Power series disconnect switch	127701CPS
	UPC
	194006020633
<b>Product Length/Depth</b>	<b>Product Height</b>
10.75 in	4.375 in
<b>Product Width</b>	<b>Product Weight</b>
30 in	46.296 lb
<b>Compliances</b>	<b>Certifications</b>
Not Applicable	IEEE C37.34

## Accessories

### Terminal options

Tin-plated 2-hole NEMA terminal pads

## Description

### Backstrap options

Standard 15" backstrap (2-3/8" x 9" bolts)

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

2.25" B.C. porcelain

### Switch type

Disconnect switch

## Application

### Application

Distribution

## Electrical Ratings

### Amperage Rating

600 A

### Basic impulse level full wave crest

125 kV

### Phase type

Single-phase

### Voltage rating

25.8 kV

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

### Specifications and datasheets

[Eaton Specification Sheet - 127701CPS](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)