

# Eaton 127701LP

Catalog Number: 127701LP

Eaton Cooper Power series disconnect switch, Vertical or underhung, 2.25" B.C. porcelain, 125 kV, Distribution, 25.8 kV, 600 A, Parallel groove clamp, bronze, Standard 15" backstrap (2-3/8" x 9" bolts), Galvanized steel hook

## General specifications



Photo is representative

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Cooper Power series disconnect switch	127701LP
	UPC
	194006020671
<b>Product Length/Depth</b>	<b>Product Height</b>
30 in	10.75 in
<b>Product Width</b>	<b>Product Weight</b>
4.375 in	45.929 lb
<b>Compliances</b>	<b>Certifications</b>
Not Applicable	IEEE C37.34

## Accessories

### Terminal options

Parallel groove clamp, bronze

## Description

### Backstrap options

Standard 15" backstrap (2-3/8" x 9" bolts)

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

2.25" B.C. porcelain

### Switch type

Disconnect switch

## Application

### Application

Distribution

## Electrical Ratings

### Amperage Rating

600 A

### Basic impulse level full wave crest

125 kV

### Phase type

Single-phase

### Voltage rating

25.8 kV

## Loadbreak Hook

### Loadbreak hook material

Galvanized steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

### Specifications and datasheets

[Eaton Specification Sheet - 127701LP](#)