

# Eaton 127938CLR

Catalog Number: 127938CLR

Eaton Cooper Power series disconnect switch, Vertical or underhung, 2.25" B.C. porcelain, 150 kV, Station, 38.0 kV, 900 A, NEMA 2-hole terminal pads with captive bolts, REA backstrap (4-3/8" x 9" bolts), Galvanized steel hook

## General specifications



Photo is representative

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Cooper Power series disconnect switch	127938CLR
	UPC
	194006023665
<b>Product Length/Depth</b>	<b>Product Height</b>
30 in	12.75 in
<b>Product Width</b>	<b>Product Weight</b>
4.375 in	47.399 lb
<b>Compliances</b>	<b>Certifications</b>
Not Applicable	IEEE C37.34

## Accessories

### Terminal options

NEMA 2-hole terminal pads with captive bolts

## Description

### Backstrap options

REA backstrap (4-3/8" x 9" bolts)

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

2.25" B.C. porcelain

### Switch type

Disconnect switch

## Application

### Application

Station

## Electrical Ratings

### Amperage Rating

900 A

### Basic impulse level full wave crest

150 kV

### Phase type

Single-phase

### Voltage rating

38.0 kV

## Loadbreak Hook

### Loadbreak hook material

Galvanized steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

### Specifications and datasheets

[Eaton Specification Sheet - 127938CLR](#)