Eaton BAB2030I

Catalog Number: BAB2030I

Eaton BAB thermal magnetic circuit breaker,Quicklag industrial thermal-magnetic circuit breaker,Bolt-on mounting,30 A,10 kAIC,Two-pole,120/240 V,Non-Interchangeable,Q7,BAB,120/208/240 V Shunt trip

General specifications



breaker

Product Length/Depth

2.563 in

Product Width

2 in

Certifications

Warranty

1 year

UL Listed
CSA Certified

Catalog Number

BAB2030I

UPC

782114312704

Product Height

3 in

Product Weight

0.6 lb

Compliances
HACR Rated

Catalog Notes

HACR rated





Physical Attributes

Circuit breaker type

BAB

Number of poles

Two-pole

Number of wires

3

Type

Quicklag industrial thermal-magnetic circuit breaker

Performance Ratings

Amperage Rating

30 A

Interrupt rating

10 kAIC

Phase

Single-phase

Trip Type

Interchangeable

Voltage rating

120/240 V

Miscellaneous

Quantity

7

Shunt trip

120-240V

Special features

Bolt-on mounting

Used with

Distribution panels 240 V (Three-phase, four-wire maximum)

Resources

Brochures

Loadcenters and Circuit Breakers

Multimedia

Circuit Breakers Explained

Specifications and datasheets

Eaton Specification Sheet - BAB2030I

Switchboards—Low Voltage



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.









Eaton.com/socialmedia