

# Eaton BQC240230

Catalog number: BQC240230

Eaton BR thermal magnetic circuit breaker, Type BQC 1-Inch CTL plug-on circuit breaker, Includes rejection tab feature, (1) Two-Pole 40 A, (1) Two-Pole 30 A, 10 kAIC, Four-pole, 120/240V, BQC, Common breaker trip, #14-4 AWG Cu/Al, BQC



## General specifications

### Product Name

Eaton BR thermal magnetic circuit breaker

### Catalog Number

BQC240230

### UPC

786676006248

### Product Length/Depth

3 in

### Product Height

3 in

### Product Width

2 in

### Product Weight

.9 lb

### Warranty

Limited lifetime residential, 1 year commercial

### Compliances

Federal Specifications Classification W-C375

### Certifications

UL 489

### Catalog Notes

All Type BD Duplex and BQ Quadplex circuit breakers carry listing for HACR applications. All 15 and 20 ampere single poles are switch duty rated.

## Physical Attributes

### Circuit breaker type

BQ

### Mounting Method

Plug-on

### Number of poles

Four-pole

### Type

Type BQC 1-Inch CTL plug-on circuit breaker

### Wire size

#14-4 AWG Cu/Al

## Performance Ratings

### Amperage Rating

(1) Two-Pole 40A, (1) Two-Pole 30A

### Interrupt rating

10 kAIC

### Trip Type

Common breaker trip

### Voltage rating

120/240 V

## Miscellaneous

### Main circuit breaker

BQC

### Special features

Includes rejection tab feature

### Used with

Type BR Loadcenters

## Resources

### Brochures

Loadcenters and Circuit Breakers

### Catalogs

Eaton's Volume 1—Residential and Light Commercial

### Specifications and datasheets

Eaton Specification Sheet - BQC240230



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2022 Eaton  
All Rights Reserved

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)