

# Eaton D73P16S0C

Catalog Number: D73P16S0C

Eaton Cooper Power series disconnect switch, Vertical or underhung, Silicone rubber, 110 kV, Distribution, 15.0 kV, 600 A, NEMA 2-hole terminal pads with captive bolts, 15" backstrap w/ two mounting bolts, Galvanized steel hook

## General specifications

|   |                |
|---|----------------|
| Product Name                                | Catalog Number |
| Eaton Cooper Power series disconnect switch | D73P16S0C      |
|   | UPC            |
|   | 194006081986   |
| Product Length/Depth                        | Product Height |
| 5 in  | 30 in          |
| Product Width                               | Product Weight |
| 8.4 in                                      | 0.001 lb       |
| Compliances                                 | Certifications |
| Not Applicable                              | IEEE C37.30.1  |

## Accessories

### Terminal options

NEMA 2-hole terminal pads with captive bolts

## Description

### Backstrap options

15" backstrap w/ two mounting bolts

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

Silicone rubber

### Switch type

Disconnect switch

## Application

### Application

Distribution

## Electrical Ratings

### Amperage Rating

600 A

### Basic impulse level full wave crest

110 kV

### Phase type

Single-phase

### Voltage rating

15.0 kV

## Loadbreak Hook

### Loadbreak hook material

Galvanized steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)