

# Eaton D73P19S0C

Catalog Number: D73P19S0C

Eaton Cooper Power series disconnect switch, Vertical or underhung  
Silicone rubber, 110 kV, Distribution, 15.0 kV, 900 A, NEMA 2-hole  
terminal pads with captive bolts, 15" backstrap w/ two mounting bolts,  
Galvanized steel hook

## General specifications

Product Name	Catalog Number
Eaton Cooper Power series disconnect switch	D73P19S0C
	UPC
	194006082358
Product Length/Depth	Product Height
5 in	30 in
Product Width	Product Weight
8.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE C37.30.1



## Accessories

### Terminal options

NEMA 2-hole terminal pads with captive bolts

## Description

### Backstrap options

15" backstrap w/ two mounting bolts

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

Silicone rubber

### Switch type

Disconnect switch

## Application

### Application

Distribution

## Electrical Ratings

### Amperage Rating

900 A

### Basic impulse level full wave crest

110 kV

### Phase type

Single-phase

### Voltage rating

15.0 kV

## Loadbreak Hook

### Loadbreak hook material

Galvanized steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)