

Eaton D73P26S0C

Catalog Number: D73P26S0C

Eaton Cooper Power series disconnect switch, Vertical or underhung
Silicone rubber, 125 kV, Distribution, 27.0 kV, 600 A, NEMA 2-hole
terminal pads with captive bolts, 15" backstrap w/ two mounting bolts,
Galvanized steel hook

General specifications

Product Name	Catalog Number
Eaton Cooper Power series disconnect switch	D73P26S0C
	UPC
	194006082631
Product Length/Depth	Product Height
5 in	30 in
Product Width	Product Weight
8.4 in	38.823 lb
Compliances	Certifications
Not Applicable	IEEE C37.30.1



Accessories

Terminal options

NEMA 2-hole terminal pads with captive bolts

Description

Backstrap options

15" backstrap w/ two mounting bolts

Blade stop options

90° blade stop, can be field-removed for 180° travel

Insulation material

Silicone rubber

Switch type

Disconnect switch

Application

Application

Distribution

Electrical Ratings

Amperage Rating

600 A

Basic impulse level full wave crest

125 kV

Phase type

Single-phase

Voltage rating

27.0 kV

Loadbreak Hook

Loadbreak hook material

Galvanized steel hook

Mounting

Mounting configuration

Vertical or underhung

Resources

Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)