# Eaton D73P36S0CE

### Catalog Number: D73P36S0CE

Eaton Cooper Power series disconnect switch, Vertical or underhung, Silicone rubber, 150 kV, Distribution, 27.0 kV, 600 A, NEMA 2-hole terminal pads with captive bolts, REA backstrap (4-3/8" x 9" bolts), Galvanized steel hook

IEEE C37.30.1

#### General specifications

Not Applicable

## Produce Eaton switch Produce 5 in Produce

Product NameCatalog NumberEaton Cooper Power series disconnectD73P36S0CEswitchUPC194006072670Product Length/DepthProduct Height5 in30 inProduct WidthProduct Weight10.8 in49.052 lbCompliancesCertifications



Powering Business Worldwide

#### Accessories

#### **Terminal options**

NEMA 2-hole terminal pads with captive bolts

#### Description

Backstrap options REA backstrap (4-3/8" x 9" bolts)

Blade stop options 90° blade stop, can be field-removed for 180° travel

Insulation material

Silicone rubber

Switch type Disconnect switch

#### Application

#### Application

Distribution

#### **Electrical Ratings**

Amperage Rating 600 A

Basic impulse level full wave crest

150 kV

Phase type

Single-phase

Voltage rating

27.0 kV

#### Loadbreak Hook

Loadbreak hook material Galvanized steel hook

#### Mounting

Mounting configuration Vertical or underhung

#### Resources

Brochures
D73P Disconnect and By-Pass Switches Catalog

Specifications and datasheets Eaton Specification Sheet - D73P36S0CE



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia