

# Eaton D73P39S0E-SS

Catalog Number: D73P39S0E-SS

Eaton Cooper Power series disconnect switch, Vert or under, Sil rub, 150 kV, Dist, 27.0 kV, 900 A, Tin-pltd 2-hole NEMA term pads, REA bckstrp w/ 4 mntng bolts, stainless steel hook, coastal

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Cooper Power series disconnect switch	D73P39S0E-SS
	UPC
	194006111133
<b>Product Length/Depth</b>	<b>Product Height</b>
5 in	30 in
<b>Product Width</b>	<b>Product Weight</b>
10.8 in	0.001 lb
<b>Compliances</b>	<b>Certifications</b>
Not Applicable	IEEE C37.30.1

## Accessories

### Special features

Stainless steel coastal

### Terminal options

Tin-plated 2-hole NEMA terminal pads

## Application

### Application

Distribution

## Description

### Backstrap options

REA backstrap (4-3/8" x 9" bolts)

### Blade stop options

90° blade stop, can be field-removed for 180° travel

### Insulation material

Silicone rubber

### Switch type

Disconnect switch

## Electrical Ratings

### Amperage Rating

900 A

### Basic impulse level full wave crest

150 kV

### Phase type

Single-phase

### Voltage rating

27.0 kV

## Loadbreak Hook

### Loadbreak hook material

Stainless steel hook

## Mounting

### Mounting configuration

Vertical or underhung

## Resources

### Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

### Specifications and datasheets

[Eaton Specification Sheet - D73P39S0E-SS](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)