

Eaton D73P56S0P

Catalog Number: D73P56S0P

Eaton Cooper Power series disconnect switch, Vert undrhng, Sil rub, 200 kV BIL, Dist, 38.0 kV, 600 A, Tin-pltd 2-hole NEMA term pd, 15" bkstrap w/2 mntng blts, Galv stl hook, PG conn

General specifications



Product Name	Catalog Number
Eaton Cooper Power series disconnect switch	D73P56S0P
	UPC
	194006091619
Product Length/Depth	Product Height
30 in	19 in
Product Width	Product Weight
5 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE C37.30.1

Accessories

Special features

Parallel groove connector

Terminal options

Tin-plated 2-hole NEMA terminal pads

Application

Application

Distribution

Description

Backstrap options

15" backstrap w/ two mounting bolts

Blade stop options

90° blade stop, can be field-removed for 180° travel

Insulation material

Silicone rubber

Switch type

Disconnect switch

Electrical Ratings

Amperage Rating

600 A

Basic impulse level full wave crest

200 kV

Phase type

Single-phase

Voltage rating

38.0 kV

Loadbreak Hook

Loadbreak hook material

Galvanized steel hook

Mounting

Mounting configuration

Vertical or underhung

Resources

Application notes

[Line installation and protective equipment product application poster](#)

Brochures

[D73P Disconnect and By-Pass Switches Catalog](#)

[Line Installation and Protective Equipment Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - D73P56SOP](#)

[Overhead line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)