Eaton D73P56SXS

Catalog Number: D73P56SXS

Eaton Cooper Power series disconnect switch, Vert undrhng, Sil rub, 200 kV BIL, Dist, 38.0 kV, 600 A, Tin-pltd 2-hole NEMA term pd, 15" bkstrap w/2 mntng blts, ss spec base, stl hook,

General specifications



Product Name Catalog Number

Eaton Cooper Power series disconnect D73P56SXS

switch

194006107242

0.001 lb

UPC

Product Length/Depth Product Height

30 in 19 in

Product Width Product Weight

Warranty Compliances
1 year Not Applicable

Certifications

5 in

IEEE C37.30.1



Accessories

Terminal options

Tin-plated 2-hole NEMA terminal pads

Application

Application

Distribution

Description

Backstrap options

15" backstrap w/ two mounting bolts

Blade stop options

90° blade stop, can be field-removed for 180° travel

Insulation material

Silicone rubber

Switch type

Disconnect switch

Electrical Ratings

Amperage Rating

600 A

Basic impulse level full wave crest

200 kV

Phase type

Single-phase

Voltage rating

38.0 kV

Loadbreak Hook

Loadbreak hook material

Stainless steel hook

Mounting

Mounting configuration

Vertical or underhung

Resources

Brochures

D73P Disconnect and By-Pass Switches Catalog

Specifications and datasheets

Eaton Specification Sheet - D73P56SXS



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.









Eaton.com/socialmedia