# Eaton M1G03FC2TU

## Catalog Number: M1G03FC2TU

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hookstick Oper. (no cntrl rod), Cycloaliphatic epx, Fbrgls-1 pt lft, grd conn on X-arm mtg brkt, Parallel Groove, Hrz uprt (G095), No hndl

### General specifications

Product Name

Eaton Cooper Power series M-Force M1G03FC2TU

three-phase switch

UPC

Catalog Number

786689709044

Product Length/Depth Product Height

106 in 22.5 in

Product Width Product Weight

22.4 in 0.001 lb

Compliances Certifications

Not Applicable IEEE Std C37.34

IEEE Std 1247





### Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Steel - single point lift

Insulator bolt pattern

2.25" BC

Material type

Cycloaliphatic epoxy

Switch type

M-Force switch

### **Electrical Ratings**

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

### M-Force Switch

M-force - optional configurations

Ground connector on x-arm, parallel groove connector

Mounting configuration (M-force only)

Horizontal upright (G095 spacing)

Operating handle configuration (M-force only)

No handle

#### Resources

**Brochures** 

M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1G03FC2TU

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



