Eaton M1G03SC3ATU

Catalog Number: M1G03SC3ATU

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 3.00" BC, Hookstick Oper. (no cntrl rod), Cycloaliphatic epx, Stl-2 pt lft, Grd connector on X-arm mtg brkt, parallel groove #2-500 MCM, Hrz uprt (G095), No hndl

General specifications

Product Name

Eaton Cooper Power series M-Force M1G03SC3ATU

three-phase switch

UPC

194006014243

Product Height

Catalog Number

Product Length/Depth

106 in 22.5 in

Product Width

Product Weight

22.4 in 0.001 lb

Compliances

Certifications

Not Applicable IEEE Std C37.34

IEEE Std 1247





Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Steel - two point lift

Insulator bolt pattern

3.00" BC

Material type

Cycloaliphatic epoxy

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Grd connector on X-arm mtg brkt, parallel groove #2-500 MCM

Mounting configuration (M-force only)

Horizontal upright (G095 spacing)

Operating handle configuration (M-force only)

No handle

Resources

Brochures

M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1G03SC3ATU

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



