

Eaton M1G11FC2HS-X045

Catalog Number: M1G11FC2HS-X045

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' Rnd pipe 1.0" OD, C-A epX, Fbrgls-2 pt lft, Ltng arrstr brkts ice shld 120" cross arm ph unit end mid ph same rel pos cnt, Hrzt uprt G095, Recip hnd

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1G11FC2HS-X045
	UPC
	194006015028
Product Length/Depth	Product Height
128 in	22.5 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std C37.34
	IEEE Std 1247

Description

Control rod and mechanism

28' round pipe 1.0" O.D.

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Cycloaliphatic epoxy

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brkts, ice shields, 120" cross arm, move end phase units to end, leave middle phase at same relative position from center

Mounting configuration (M-force only)

Horizontal upright (G095 spacing)

Operating handle configuration (M-force only)

Reciprocating

Resources

Brochures

M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1G11FC2HS-X045



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia