

Eaton M1G51FC2HS

Catalog Number: M1G51FC2HS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' pipe w/cycloaliphatic Ins., Cycloaliphatic epoxy, Fbrgls-2 pt lft, Lightning arrester brkts, ice shields, Hrzt uprt (G095 space), Reciprocating

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1G51FC2HS
	UPC
	194006015042
Product Length/Depth	Product Height
106 in	22.5 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std 1247
	IEEE Std C37.34

Description

Control rod and mechanism

28' pipe w/cycloaliphatic insulator

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Cycloaliphatic epoxy

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brkts, ice shields

Mounting configuration (M-force only)

Horizontal upright (G095 spacing)

Operating handle configuration (M-force only)

Reciprocating

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1G51FC2HS](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)