

Eaton M1GB2FR2HX

Catalog Number: M1GB2FR2HX

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (Fbrgls univsl sect), Slcn rubber, Fbrgls-2 pt lft, Lightning arrester brkts, addtl bond wire tors hndl, Hrzt uprt (G095 space), Trsnl hndl

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1GB2FR2HX
	UPC
	194006110952
Product Length/Depth	Product Height
106 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std 1247
	IEEE Std C37.34

Description

Control rod and mechanism

28' 1" pipe w/fiberglass top section

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brkts, additional bond wire for torsional handle

Mounting configuration (M-force only)

Horizontal upright (G095 spacing)

Operating handle configuration (M-force only)

Torsional

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1GB2FR2HX](#)