Eaton M1GB2SC2HS

Catalog Number: M1GB2SC2HS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' 1.5" pipe (Fbrgls univsl sect), Cycloaliphatic epoxy, Stl-2 pt lft, Lightning arrester brkts, ice shields, Hrz uprt (G095 space), Torsional

General specifications

Product Name

Eaton Cooper Power series M-Force three-phase switch

Product Length/Depth 106 in Product Width 22.4 in

Compliances Not Applicable M1GB2SC2HS UPC 194006015080 Product Height

Catalog Number

22.5 in

Product Weight 0.001 lb

Certifications IEEE Std C37.34

IEEE Std 1247



Description

Control rod and mechanism

28' 1.5" pipe (fiberglass universal section)

Crossarm material

Steel - two point lift

Insulator bolt pattern 2.25" BC

Material type Cycloaliphatic epoxy

Switch type M-Force switch

Electrical Ratings

Amperage Rating 900A Basic impulse level 110 kV Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations Lightning arrester brkts, ice shields

Mounting configuration (M-force only) Horizontal upright (G095 spacing)

Operating handle configuration (M-force only) Torsional

Resources

Brochures M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1GB2SC2HS



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

© 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia