Eaton M1H03FC2AS

Catalog Number: M1H03FC2AS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hookstick operated (no control rod), Cycloaliphatic epoxy, Fiberglass - 2 point lift, Ice shields, Ex 14' of control rod, Horizontal upright, No handle

General specifications

Product Name

M1H03FC2AS Eaton Cooper Power series M-Force three-phase switch Product Length/Depth 88 in 22.5 in **Product Width**

22.4 in

Compliances Not Applicable UPC 194006015127 **Product Height**

Catalog Number

Product Weight 0.001 lb

Certifications

IEEE Std 1247 IEEE Std C37.34





Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material Fiberglass - two point lift

Insulator bolt pattern 2.25" BC

Material type Cycloaliphatic epoxy

Switch type M-Force switch

Electrical Ratings

Amperage Rating 900A Basic impulse level 110 kV Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations Ice shields, extra 14' of control rod

Mounting configuration (M-force only) Horizontal upright

Operating handle configuration (M-force only) No handle

Resources

Brochures M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1H03FC2AS



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia