Eaton M1H03FC2HS

Catalog Number: M1H03FC2HS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hookstick Oper. (no cntrl rod), Cycloaliphatic epoxy, Fiberglass - 2 point lift, Lightning arrester brkts, ice shields, Horizontal upright, No handle

General specifications

Product Name

Catalog Number

Eaton Cooper Power series M-Force

M1H03FC2HS

three-phase switch

UPC

194006016346

Product Length/Depth

Product Height

88 in

22.5 in

Product Width

Product Weight

22.4 in

0.001 lb

Compliances

Certifications

Not Applicable

IEEE Std 1247 IEEE Std C37.34



Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Cycloaliphatic epoxy

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brkts, ice shields

Mounting configuration (M-force only)

Horizontal upright

Operating handle configuration (M-force only)

No handle

Resources

Brochures

M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1H03FC2HS

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.









