

Eaton M1H03FR3T

Catalog Number: M1H03FR3T

Eaton Cooper Power Series M-Force 3-Phase Gang operated Switch, 15KV, 900A, Hrzs Up, SiRub Ins, 3" BC, FibGls X-arm, 2 pt lift, hook-stick/bellcrank, Grd Conn on X-arm mtg bkt

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H03FR3T
	UPC
	786689709259
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std C37.34
	IEEE Std 1247

Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

3.00" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Grd connector on x-arm mtg bracket

Mounting configuration (M-force only)

Horizontal upright (standard option)

Operating handle configuration (M-force only)

No handle

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1H03FR3T](#)