

Eaton M1H03GC2HS

Catalog Number: M1H03GC2HS

Eaton Cooper Power Series M-Force 3-Phase Gang operated Switch, 15KV, 900A, Hrз Up, SiRub Ins, 2.25" BC, FibGls X-arm, 2 pt lft, hook-stick/bellcrank, lltng arrest brkt, ice shield

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H03GC2HS
	UPC
	194006117678
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std 1247
	IEEE Std C37.34

Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brackets, ice shields

Mounting configuration (M-force only)

Horizontal upright (standard option)

Operating handle configuration (M-force only)

No handle

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1H03GC2HS](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)