

Eaton M1H03GR2U

Catalog Number: M1H03GR2U

Eaton Cooper Power Series M-Force 3-Phase Gang operated Switch, 15KV, 900A, Hrз Up, SiRub Ins, 2.25" BC, FibGls X-arm, 2 pt lft, hook-stick/bellcrank, Par grv conn

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H03GR2U
	UPC
	194006088466
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std C37.34
	IEEE Std 1247

Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Parallel groove connector

Mounting configuration (M-force only)

Horizontal upright (standard option)

Operating handle configuration (M-force only)

No handle

Resources

Application notes

[Line installation and protective equipment product application poster](#)

Specifications and datasheets

[Eaton Specification Sheet - M1H03GR2U](#)

[Line installation and protective equipment specifiers guide](#)

[Overhead line installation and protective equipment specifiers guide](#)

[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)