Eaton M1H03TR2AAHT

Catalog Number: M1H03TR2AAHT

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hookstick Oper. (no cntrl rod), Silicone rubber, Stl-1 pt lft, Lightning arrester brkts, grd connector on X-arm mtg brkt, Hrz uprt, No handle

General specifications

Product Name

Eaton Cooper Power series M-Force three-phase switch

Product Length/Depth 88 in

Product Width

22.4 in

Compliances Not Applicable M1H03TR2AAHT UPC 194006016414 Product Height

Catalog Number

23.9 in

Product Weight 0.001 lb

Certifications

IEEE Std 1247 IEEE Std C37.34





Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Steel - single point lift

Insulator bolt pattern

2.25" BC

Material type Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating 900A Basic impulse level 110 kV Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester brkts, grd connector on X-arm mtg brkt

Mounting configuration (M-force only) Horizontal upright

Operating handle configuration (M-force only) No handle

Resources

Brochures M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M1H03TR2AAHT



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Righ Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia