

Eaton M1H03TR2BHS

Catalog Number: M1H03TR2BHS

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hkstick Op, Slcn rub, Stl-1 pt lft, prv xarm brcs, ltg arrst brkt, ice shld, Hz up, No hndl

General specifications



| Product Name | Catalog Number |
|--|----------------|
| Eaton Cooper Power series M-Force three-phase switch | M1H03TR2BHS |

UPC
194006125208

Product Length/Depth
88 in

Product Height
23.9 in

Product Width
22.4 in

Product Weight
0.001 lb

Compliances
Not Applicable

Certifications
IEEE Std C37.34
IEEE Std 1247

Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Steel - single point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Provisions for crossarm support braces, lightning arrester brackets, ice shields

Mounting configuration (M-force only)

Horizontal upright

Operating handle configuration (M-force only)

No handle

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Installation instructions

[Manually-Operated M-Force Switch Installation and Operation Instructions](#)

Specifications and datasheets

[Overhead line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)