

Eaton M1H03TR2STU

Catalog Number: M1H03TR2STU

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, Hookstick Oper. (no cntrl rod), Slcn rub, Stl-1 pt lft,ice shld, grd connector on X-arm mtg brkt, PG conn, Hrzt uprt, No hndl

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H03TR2STU
	UPC
	194006088329
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std C37.34
	IEEE Std 1247

Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material

Steel - single point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Ice shield kit, grd connector on X-arm mtg brkt, parallel groove connector

Mounting configuration (M-force only)

Horizontal upright

Operating handle configuration (M-force only)

No handle

Resources

Application notes

[Line installation and protective equipment product application poster](#)

Brochures

[M-Force Three-Phase Switch Catalog](#)

Specifications and datasheets

[Eaton Specification Sheet - M1H03TR2STU](#)

[Overhead line installation and protective equipment specifiers guide](#)

[Line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)