

Eaton M1H11FR2HJRT

Catalog Number: M1H11FR2HJRT

Eaton Cooper Power series M-Force three-phase switch, 15.5 kV, 900A, 110 kV, 2.25" BC, 28' rnd pipe 1.0" O.D, Sil rub, FG- 2pt lft, ltng arstr brkts,prv neut sens, nmplt on hndl, grn cnn xarm mt brkt ,Hrz up, recip

General specifications



Product Name	Catalog Number
Eaton Cooper Power series M-Force three-phase switch	M1H11FR2HJRT
	UPC
	194006124553
Product Length/Depth	Product Height
88 in	23.9 in
Product Width	Product Weight
22.4 in	0.001 lb
Compliances	Certifications
Not Applicable	IEEE Std 1247
	IEEE Std C37.34

Description

Control rod and mechanism

28' round pipe 1.0" O.D.

Crossarm material

Fiberglass - two point lift

Insulator bolt pattern

2.25" BC

Material type

Silicone rubber

Switch type

M-Force switch

Electrical Ratings

Amperage Rating

900A

Basic impulse level

110 kV

Number of phases

Three-phase

Voltage rating

15.5 kV

M-Force Switch

M-force - optional configurations

Lightning arrester bracket, Provisions for Neutral Wire, additional nameplate on handle, Grounding Connector on Crossarm Mounting Bracket

Mounting configuration (M-force only)

Horizontal upright (standard option)

Operating handle configuration (M-force only)

Reciprocating

Resources

Brochures

[M-Force Three-Phase Switch Catalog](#)

Installation instructions

[Manually-Operated M-Force Switch Installation and Operation Instructions](#)

Specifications and datasheets

[Eaton Specification Sheet - MIH11FR2HJRT](#)

[Overhead line installation and protective equipment specifiers guide](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)