

# Product datasheet

Specifications



mini Kaedra - for modular device -  
1 openings - 8 modules - 4  
terminal blocks

13443

## Main

Range	Mureva
Product Name	Mureva Enclosure
Product Or Component Type	Weatherproof enclosure
Enclosure Type	Mini enclosure for modular device
Mounting Plate Description	Without mounting plate

## Complementary

Enclosure Mounting	Surface
9 Mm Pitches	16
Number Of 18 Mm Modules Per Row	8
Total Number Of 18 Mm Modules	8
Number Of Horizontal Rows	1
Electrical Insulation Class	Class II Double insulation
Provided Equipment	1 marking kit 4 terminal block 4 holes
Type Of Front Cover	Transparent
Power Dissipation In W	15 W
[In] Rated Current	63 A
Type Of Rail	DIN
Number Of Pre-Cutouts Pg Iso	5
Number Of Terminal Blocks	4 earth / neutral (screw connection) with 4 outgoers
Distribution Block Outgoers	8 x 10 mm <sup>2</sup> 8 x 16 mm <sup>2</sup>
Locking Options Description	Optional keylock
Enclosure Material	Self-extinguishing polymer
Width	195 mm
Height	200 mm
Depth	112 mm
Internal Depth	56 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

<b>Standards</b>	IEC 60670 IEC 60695-2-1 EN 50262 IEC 61439-3
<b>Fire Resistance</b>	650 °C conforming to IEC 60695-2-1
<b>Ip Degree Of Protection</b>	IP65 conforming to IEC 60529
<b>Ik Degree Of Protection</b>	IK09 conforming to EN 50102
<b>Environmental Characteristics (Uv)</b>	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
<b>Overvoltage Category</b>	II
<b>Ambient Air Temperature For Operation</b>	-25...60 °C

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	6.000 cm
<b>Package 1 Width</b>	24.500 cm
<b>Package 1 Length</b>	26.000 cm
<b>Package 1 Weight</b>	740.000 g
<b>Unit Type Of Package 2</b>	CAR
<b>Number Of Units In Package 2</b>	6
<b>Package 2 Height</b>	22.000 cm
<b>Package 2 Width</b>	34.500 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	4.750 kg
<b>Unit Type Of Package 3</b>	P12
<b>Number Of Units In Package 3</b>	144
<b>Package 3 Height</b>	80.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	129.120 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Lower Impact Materials Transparency RoHS/REACH

## Resource performance

✓ Minimum Percentage Of Recycled Plastic Content 25

## Well-being performance

✓ Rohs Exemption Information Yes

✓ Halogen Free Product

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations