

# Product data sheet

Specifications



## IEC contactor, Easy TeSys DPE, nonreversing, 38A, 3P, 20HP at 480V AC, 120V 50/60Hz coil

DPE38G7

**Product availability : Stock - Normally stocked in distribution facility**

**Price\* : 57.00 USD**

### Main

Range	Easy TeSys
Product name	Easy TeSys DPE
Product or Component Type	Contactors
Device short name	DPE
Contactors application	Resistive load Motor control
Utilisation category	AC-4 AC-1 AC-3
Poles description	3P
Maximum Operational Voltage	Power circuit <= 690 V AC 25...400 Hz Power circuit <= 300 V DC
[Ie] rated operational current	38 A 140 °F (60 °C) <= 440 V AC AC-3 power circuit 52 A 140 °F (60 °C) <= 440 V AC AC-1 power circuit
[Uc] control circuit voltage	120 V AC 50/60 Hz

### Complementary

Motor power kW	9 kW 220...230 V AC 50/60 Hz 18.5 kW 380...400 V AC 50/60 Hz 18.5 kW 415 V AC 50/60 Hz 18.5 kW 440 V AC 50/60 Hz 18.5 kW 500 V AC 50/60 Hz 18.5 kW 660...690 V AC 50/60 Hz
Maximum Horse Power Rating	2 hp 115 V at AC 50/60 Hz for 1 phase 5 hp 230/240 V at AC 50/60 Hz for 1 phase 10 hp 200/208 V at AC 50/60 Hz for 3 phase 10 hp 230/240 V at AC 50/60 Hz for 3 phase 20 hp 460/480 V at AC 50/60 Hz for 3 phase 25 hp 575/600 V at AC 50/60 Hz for 3 phase
Pole contact composition	3 NO
Control circuit type	AC 50/60 Hz
Auxiliary contact composition	1 NO
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Overvoltage category	III
[Ith] conventional free air thermal current	10 A 140 °F (60 °C) signalling circuit 50 A 140 °F (60 °C) power circuit
Irms rated making capacity	140 A AC signalling circuit IEC 60947-5-1

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

250 A DC signalling circuit IEC 60947-5-1  
550 A 440 V power circuit IEC 60947

<b>Rated breaking capacity</b>	550 A 440 V power circuit IEC 60947
<b>Associated fuse rating</b>	10 A gG signalling circuit IEC 60947-5-1 63 A gG ≤ 690 V type 1 power circuit 63 A gG ≤ 690 V type 2 power circuit
<b>Average impedance</b>	2 mOhm - lth 50 A 50 Hz power circuit
<b>[Ui] rated insulation voltage</b>	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1
<b>Electrical durability</b>	1 Mcycles 38 A AC-3 ≤ 440 V 0.6 Mcycles 52 A AC-1 ≤ 440 V
<b>Power dissipation per pole</b>	2 W AC-3 5 W AC-1
<b>Mounting Support</b>	Rail Plate
<b>Connections - terminals</b>	Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible with cable end Power circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end Power circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible without cable end Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) flexible with cable end Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> ) flexible with cable end Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> ) solid without cable end
<b>Tightening torque</b>	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2
<b>Operating time</b>	12...22 ms closing 4...19 ms opening
<b>Safety reliability level</b>	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
<b>Mechanical durability</b>	10 Mcycles
<b>Maximum operating rate</b>	3600 cyc/h 140 °F (60 °C)
<b>Coil technology</b>	Without built-in suppressor module
<b>Control circuit voltage limits</b>	Drop-out 0.3...0.6 Uc 50/60 Hz 158 °F (70 °C)) Operational 0.8...1.1 Uc 50 Hz 140 °F (60 °C)) Operational 0.85...1.1 Uc 60 Hz 140 °F (60 °C)) Operational 1...1.1 Uc 50/60 Hz 158 °F (70 °C))
<b>Inrush power in VA</b>	70 VA 60 Hz 0.75 68 °F (20 °C)) 70 VA 50 Hz 0.75 68 °F (20 °C))
<b>Hold-in power consumption in VA</b>	7.5 VA 60 Hz 0.3 68 °F (20 °C)) 7 VA 50 Hz 0.3 68 °F (20 °C))
<b>Auxiliary contacts type</b>	Mechanically linked 1 NO IEC 60947-5-1
<b>Signalling circuit frequency</b>	25...400 Hz
<b>Minimum switching current</b>	5 mA signalling circuit
<b>Minimum switching voltage</b>	17 V signalling circuit
<b>Insulation resistance</b>	> 10 MOhm signalling circuit
<b>Mechanical robustness</b>	Vibrations contactor open 2 Gn, 5...300 Hz) Vibrations contactor closed 4 Gn, 5...300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)
<b>Height</b>	3.35 in (85 mm)
<b>Width</b>	1.77 in (45 mm)
<b>Depth</b>	3.62 in (92 mm)
<b>Net Weight</b>	0.83 lb(US) (0.375 kg)

<b>Non-overlap time</b>	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
-------------------------	---

## Environment

<b>Standards</b>	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-4-1
<b>Product Certifications</b>	UL CSA
<b>Heat dissipation</b>	2...3 W 50/60 Hz
<b>IP degree of protection</b>	IP20 front face IEC 60529
<b>Pollution degree</b>	3
<b>Protective treatment</b>	TH IEC 60068-2-30
<b>Ambient air temperature for operation</b>	-40...140 °F (-40...60 °C)
<b>Ambient Air Temperature for Storage</b>	-76...176 °F (-60...80 °C)
<b>Operating altitude</b>	0...6561.68 ft (0...2000 m)
<b>Flame retardance</b>	V1 conforming to UL 94
<b>Fire resistance</b>	1562 °F (850 °C) IEC 60695-2-1

## Ordering and shipping details

<b>Category</b>	22362-EASY TESYS DPE1
<b>Discount Schedule</b>	I13
<b>GTIN</b>	3606481063267
<b>Nbr. of units in pkg.</b>	1
<b>Package weight(Lbs)</b>	14.11 oz (400.0 g)
<b>Returnability</b>	Yes
<b>Country of origin</b>	ID

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Package 1 Height</b>	3.98 in (10.1 cm)
<b>Package 1 width</b>	1.77 in (4.5 cm)
<b>Package 1 Length</b>	3.35 in (8.5 cm)
<b>Unit Type of Package 2</b>	S02
<b>Number of Units in Package 2</b>	16
<b>Package 2 Weight</b>	14.80 lb(US) (6.715 kg)
<b>Package 2 Height</b>	5.91 in (15.0 cm)
<b>Package 2 width</b>	11.81 in (30.0 cm)
<b>Package 2 Length</b>	15.75 in (40.0 cm)
<b>Unit Type of Package 3</b>	P06
<b>Number of Units in Package 3</b>	256
<b>Package 3 Weight</b>	255.60 lb(US) (115.94 kg)
<b>Package 3 Height</b>	303.15 in (770.0 cm)

<b>Package 3 width</b>	23.62 in (60.0 cm)
<b>Package 3 Length</b>	31.50 in (80.0 cm)

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>