

Switchgear, HVL switch, 600A, 15 kV, 3 pole, switched fuse mechanism, 125A to 200A E DIN/E current limit fuse, NEMA 3R

HVL315DEW2

Price\*: 23,978.00 USD

#### Main

Product	Switched fuse mechanism
Included Accessory	Enclosure heater
Not Included	fuse to be ordered separately

## Complementary

Protection type	Fuse current limiter
Associated fuse rating	125 A E 150 A E 175 A E 200 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Frequency	50/60 Hz
Number of Poles	3P
[Ur] highest voltage for equipment	15 kV
Basic Inulation Level	90 kV
Enclosure Rating	NEMA 3R
Electrical connection	Lugs
Type of Installation	Outdoor
Wire Gauge	AWG 2600 kcmil aluminium/copper
Enclosure Width	38 in (965.20 mm)
Enclosure Depth	60 in (1524.00 mm)
Enclosure Height	97 in (2463.80 mm)

#### **Environment**

Product certifications	cUL
	UL Listed

### Ordering and shipping details

Category	07945-15KV N3R DIGEST HVL	
----------	---------------------------	--

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Discount Schedule	PE5A
Package weight(Lbs)	1200.00 lb(US) (544.311 kg)
Returnability	No

# **Contractual warranty**

Warranty	18 months
----------	-----------