

Product datasheet

Specifications



10A TAPOFF UNITS

KBC10DCS301



Main

Range	Canalis
Product or component type	Tap-off unit
Device short name	KBC
Product compatibility	KBA KDP KBB
Device application	Lighting
Range compatibility	KBA busbar trunking KBB busbar trunking KDP busbar trunking

Complementary

[Ue] rated operational voltage	230...240 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	10 A at 35 °C
Network frequency	50/60 Hz
Protection type	Without protection
Electrical connection	Pre-wired with SO5Z1Z1-F - 3 x 1.5 mm ² for 0.8 m long
Busbar trunking polarity	L1 + N + PE L2 + L1 + L3 + N + PE
Tap-off unit polarity	L3+N
Tap-off unit connector type	With fixed polarity
Tap-off lock colour	Brown
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	55 mm
Depth	12.5 mm
Height	42 mm
Colour	Cream (RAL 9001)
Net weight	100 g
Quantity per set	Set of 10

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
------------------------------	---

Package 1 Weight	81.0 g
------------------	--------

Package 1 Height	3.5 cm
------------------	--------

Package 1 width	4 cm
-----------------	------

Package 1 Length	6 cm
------------------	------

Unit Type of Package 2	BB1
------------------------	-----

Number of Units in Package 2	10
------------------------------	----

Package 2 Weight	912.0 g
------------------	---------

Package 2 Height	10 cm
------------------	-------

Package 2 width	14.5 cm
-----------------	---------

Package 2 Length	39.5 cm
------------------	---------

Unit Type of Package 3	P12
------------------------	-----

Number of Units in Package 3	960
------------------------------	-----

Package 3 Weight	99.552 kg
------------------	-----------

Package 3 Height	73.5 cm
------------------	---------

Package 3 width	80 cm
-----------------	-------

Package 3 Length	120 cm
------------------	--------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
-----------------------	---

Environmental Disclosure	Product Environmental Profile
--------------------------	---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

PVC free	Yes
----------	-----

Halogen content performance	Halogen free plastic parts product
-----------------------------	------------------------------------

Contractual warranty

Warranty	18 months
----------	-----------

