

# Product datasheet

Specifications



## Canalis - tap-off unit - 16A - 3L+N +PE - with protection

KBC16DCF40

### Main

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBA KBB
Device application	Lighting
Range compatibility	KBB busbar trunking KBA busbar trunking

### Complementary

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Busbar trunking polarity	L2 + L1 + L3 + N + PE
Protection type	Fuse
Fuse type	Cylindrical: 8.5 x 31.5 mm - gG conforming to NF
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Provided equipment	Fuse not supplied
Standards	EN/IEC 60439-2 EN/IEC 61439-6
Width	205 mm
Depth	38 mm
Height	68 mm
Colour	Cream (RAL 9001)
Net weight	90 g

### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	229.0 g
Package 1 Height	7.5 cm
Package 1 width	8 cm
Package 1 Length	17 cm
Unit Type of Package 2	P06
Number of Units in Package 2	144
Package 2 Weight	38.976 kg
Package 2 Height	73 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	BB1
Number of Units in Package 3	18
Package 3 Weight	4.613 kg
Package 3 Height	15.8 cm
Package 3 width	28.5 cm
Package 3 Length	43.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------

