


# Product datasheet

Specifications



## Canalis - tap-off unit - 16A - 3L+N+PE - VDE power socket - with protection

KBC16DCP2

### Main

Range	Canalis
Product or component type	Tap-off unit
Product compatibility	KBB KBA
Device application	Power socket distribution
Range compatibility	KBB busbar trunking KBA busbar trunking

### Complementary

[Ue] rated operational voltage	230...400 V
[Ui] rated insulation voltage	690 V
[Ie] rated operational current	16 A at 35 °C
Network frequency	50/60 Hz
Busbar trunking polarity	L2 + L1 + L3 + N + PE
Protection type	Fuse
Fuse type	Cylindrical: 8.5 x 31.5 mm - gG conforming to NF
Tap-off unit polarity	3L+N+PE
Tap-off unit connector type	With fixed polarity
Tap-off unit socket description	VDE 2P+E 10/16 A 250V
Provided equipment	Fuse not supplied
Standards	EN/IEC 61439-6 EN/IEC 60439-2
Width	160 mm
Depth	53 mm
Height	68 mm
Colour	White (RAL 9003)
Net weight	90 g

### Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
-------------------------	---------------------------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	250.0 g
Package 1 Height	7.5 cm
Package 1 width	8 cm
Package 1 Length	16 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	250.0 g
Package 2 Height	8 cm
Package 2 width	8.5 cm
Package 2 Length	17.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------

