

Product data sheet

Specifications



IEC contactor, TeSys D,
nonreversing, 40A, 30HP at
480VAC, up to 100kA SCCR, 3
phase, 3 NO, 120VAC 50/60Hz
coil, open

LC1D40G7M

Product availability: Stock - Normally stocked in distribution facility

Price*: 361.20 USD

Main

Range	TeSys
Range Of Product	TeSys Deca
Product Or Component Type	Contactors
Device Short Name	LC1D
Contactors Application	Resistive load Motor control
Utilisation Category	AC-1 AC-4 AC-3 AC-3e
Poles Description	3P
[Ue] Rated Operational Voltage	Power circuit <= 690 V AC 25...400 Hz
[Ie] Rated Operational Current	60 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 40 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit
[Uc] Control Circuit Voltage	120 V AC 50/60 Hz

Complementary

Motor Power Kw	18.5 kW at 380...400 V AC 50/60 Hz (AC-3) 22 kW at 500 V AC 50/60 Hz (AC-3) 30 kW at 660...690 V AC 50/60 Hz (AC-3) 22 kW at 1000 V AC 50/60 Hz (AC-3) 22 kW at 415 V AC 50/60 Hz (AC-3) 22 kW at 440 V AC 50/60 Hz (AC-3) 11 kW at 220...230 V AC 50/60 Hz (AC-3) 9 kW at 400 V AC 50/60 Hz (AC-4) 18.5 kW at 380...400 V AC 50/60 Hz (AC-3e) 22 kW at 500 V AC 50/60 Hz (AC-3e) 30 kW at 660...690 V AC 50/60 Hz (AC-3e) 22 kW at 1000 V AC 50/60 Hz (AC-3e) 22 kW at 415 V AC 50/60 Hz (AC-3e) 22 kW at 440 V AC 50/60 Hz (AC-3e) 11 kW at 220...230 V AC 50/60 Hz (AC-3e)
----------------	---

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Maximum Horse Power Rating	10 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to CSA 10 hp at 200/208 V AC 60 Hz for 3 phase motors conforming to UL 10 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to CSA 10 hp at 230/240 V AC 60 Hz for 3 phase motors conforming to UL 5 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to CSA 5 hp at 230/240 V AC 60 Hz for 1 phase motors conforming to UL 3 hp at 115 V AC 60 Hz for 1 phase motors conforming to CSA 3 hp at 115 V AC 60 Hz for 1 phase motors conforming to UL 30 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to CSA 30 hp at 460/480 V AC 60 Hz for 3 phase motors conforming to UL 30 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to CSA 30 hp at 575/600 V AC 60 Hz for 3 phase motors conforming to UL
Compatibility Code	LC1D
Pole Contact Composition	3 NO
Protective Cover	Without
[Ith] Conventional Free Air Thermal Current	60 A (at 140 °F (60 °C)) for power circuit 10 A (at 140 °F (60 °C)) for signalling circuit
Irms Rated Making Capacity	800 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated Breaking Capacity	800 A at 440 V for power circuit conforming to IEC 60947
Associated Fuse Rating	80 A gG at <= 690 V coordination type 1 for power circuit 80 A gG at <= 690 V coordination type 2 for power circuit 10 A gG for signalling circuit conforming to IEC 60947-5-1
Power Dissipation Per Pole	5.4 W AC-1 2.4 W AC-3 2.4 W AC-3e
[Ui] Rated Insulation Voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 600 V CSA Signalling circuit 600 V UL Signalling circuit 690 V IEC 60947-1
Overvoltage Category	III
Pollution Degree	3
[Uimp] Rated Impulse Withstand Voltage	8 kV IEC 60947
Safety Reliability Level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Mechanical Durability	6 Mcycles
Control Circuit Type	AC 50/60 Hz
Coil Technology	Without built-in suppressor module
Control Circuit Voltage Limits	0.3...0.6 Uc -40...158 °F (-40...70 °C) drop-out AC 50/60 Hz 0.8...1.1 Uc -40...131 °F (-40...55 °C) operational AC 50 Hz 0.85...1.1 Uc -40...131 °F (-40...55 °C) operational AC 60 Hz 1...1.1 Uc 131...158 °F (55...70 °C) operational AC 50/60 Hz
Inrush Power In Va	160 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C)) 140 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-In Power Consumption In Va	15 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C)) 13 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat Dissipation	4...5 W at 50/60 Hz
Operating Time	4...19 ms opening 12...26 ms closing
Maximum Operating Rate	3600 cyc/h 140 °F (60 °C)

Connections - Terminals	<p>Power circuit: screw clamp terminals 1 0.00...0.05 in² (1...35 mm²) - cable stiffness: flexible without cable end</p> <p>Power circuit: screw clamp terminals 2 0.00...0.04 in² (1...25 mm²) - cable stiffness: flexible with cable end</p> <p>Power circuit: screw clamp terminals 1 0.00...0.05 in² (1...35 mm²) - cable stiffness: solid</p> <p>Control circuit: screw clamp terminals 1 0.00...0.01 in² (1...4 mm²) - cable stiffness: flexible without cable end</p> <p>Control circuit: screw clamp terminals 2 0.00...0.01 in² (1...4 mm²) - cable stiffness: flexible without cable end</p> <p>Control circuit: screw clamp terminals 2 0.00...0.00 in² (1...2.5 mm²) - cable stiffness: flexible with cable end</p> <p>Control circuit: screw clamp terminals 1 0.00...0.01 in² (1...4 mm²) - cable stiffness: solid</p> <p>Control circuit: screw clamp terminals 2 0.00...0.01 in² (1...4 mm²) - cable stiffness: solid</p> <p>Control circuit: screw clamp terminals 1 0.00...0.00 in² (1...2.5 mm²) - cable stiffness: flexible with cable end</p> <p>Power circuit: screw clamp terminals 2 0.00...0.05 in² (1...35 mm²) - cable stiffness: flexible without cable end</p> <p>Power circuit: screw clamp terminals 2 0.00...0.05 in² (1...35 mm²) - cable stiffness: solid</p>
Tightening Torque	<p>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal flat Ø 6 mm</p> <p>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal Philips No 2</p> <p>Power circuit 44.25 lbf.in (5 N.m) screw clamp terminal flat Ø 6 to Ø 8 mm</p> <p>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminal pozidriv No 2</p>
Auxiliary Contact Composition	1 NO + 1 NC
Auxiliary Contacts Type	Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1
Signalling Circuit Frequency	25...400 Hz
Minimum Switching Voltage	17 V for signalling circuit
Minimum Switching Current	5 mA for signalling circuit
Insulation Resistance	> 10 MOhm for signalling circuit
Non-Overlap Time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Mounting Support	Plate Rail

Environment

Standards	<p>CSA C22.2 No 14</p> <p>EN 60947-4-1</p> <p>EN 60947-5-1</p> <p>IEC 60947-4-1</p> <p>IEC 60947-5-1</p> <p>UL 508</p>
Product Certifications	<p>BV</p> <p>CCC</p> <p>CSA</p> <p>DNV</p> <p>GL</p> <p>LROS (Lloyds register of shipping)</p> <p>UL</p> <p>GOST</p> <p>RINA</p> <p>UKCA</p>
Climatic Withstand	<p>IACS E10 exposure to damp heat</p> <p>IEC 60947-1 Annex Q category D exposure to damp heat</p>
Permissible Ambient Air Temperature Around The Device	<p>-40...140 °F (-40...60 °C)</p> <p>140...158 °F (60...70 °C) with derating</p>
Operating Altitude	0...9842.52 ft (0...3000 m)
Fire Resistance	1562 °F (850 °C) IEC 60695-2-1
Flame Retardance	V1 conforming to UL 94

Mechanical Robustness	Vibrations contactor open 2 Gn, 5...300 Hz) Vibrations contactor closed 3 Gn, 5...300 Hz) Shocks contactor open 8 Gn for 11 ms) Shocks contactor closed 10 Gn for 11 ms)
Height	5.00 in (127 mm)
Width	2.95 in (75 mm)
Depth	4.69 in (119 mm)
Net Weight	3.09 lb(US) (1.4 kg)

Ordering and shipping details

Category	US101222357
Discount Schedule	0112
Gtin	3606480561351
Returnability	Yes
Country Of Origin	US

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.59 in (14.2 cm)
Package 1 Width	3.74 in (9.5 cm)
Package 1 Length	4.13 in (10.5 cm)
Package 1 Weight	3.19 lb(US) (1.449 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

✓ Pvc Free

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile No need of specific recycling operations