

Product data sheet

Specifications



Thermal overload relay, TeSys Deca, 690VAC, 23 to 32A, 1NO+1NC, class 20, screw terminal, for unbalanced loads

LR3D32L

Product availability: Stock - Normally stocked in distribution facility

Price*: 62.00 USD

Main

Range	TeSys
Product name	TeSys LRD TeSys Deca
Product or Component Type	Non differential thermal overload relay
Device short name	LR3D
Relay application	Motor protection
Product Compatibility	LC1D38 LC1D25 LC1D32
network type	DC AC
Thermal overload class	Class 20 IEC 60947-4-1
Thermal protection adjustment range	23...32 A
[Ui] rated insulation voltage	Power circuit 600 V CSA Power circuit 600 V UL Power circuit 690 V IEC 60947-4-1

Complementary

Network Frequency	0...400 Hz
Mounting support	Plate, with specific accessories Rail, with specific accessories Under contactor
Tripping threshold	1.14 +/- 0.06 Ir IEC 60947-4-1
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A signalling circuit
Permissible current	3 A 120 V AC-15 signalling circuit 0.22 A 125 V DC-13 signalling circuit
[Ue] rated operational voltage	690 V AC 0...400 Hz power circuit IEC 60947-4-1
Associated fuse rating	4 A gG for signalling circuit 4 A BS for signalling circuit
[Uimp] rated impulse withstand voltage	6 kV
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Control type	Red push-button stop Blue push-button reset

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Temperature compensation	-4.0000000000...140.0000000000 °F (-20...60 °C)
Connections - terminals	Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) flexible without cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) solid without cable end Power circuit screw clamp terminals 1 0.002...0.02 in ² (1.5...10 mm ²) flexible without cable end Power circuit screw clamp terminals 1 0.002...0.009 in ² (1...6 mm ²) flexible with cable end Power circuit screw clamp terminals 1 0.002...0.02 in ² (1.5...10 mm ²) solid without cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals
Height	2.6 in (66 mm)
Width	1.8 in (45 mm)
Depth	3.0 in (76 mm)
Net Weight	0.317 lb(US) (0.144 kg)

Environment

Climatic withstand	IACS E10
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-4.0000000000...140.0000000000 °F (-20...60 °C) without derating IEC 60947-4-1
Ambient Air Temperature for Storage	-76.0000000000...158.0000000000 °F (-60...70 °C)
Mechanical robustness	Shocks 15 Gn for 11 ms IEC 60068-2-7 Vibrations 3 GN IEC 60068-2-6
Dielectric strength	1.89 kV 50 Hz IEC 60947-1
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 EN 50495
Product Certifications	IEC UL CSA EAC ABS ATEX INERIS UKCA

Ordering and shipping details

Category	US10I1222347
Discount Schedule	0I12
GTIN	3606480609756
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.3 in (8.3 cm)

Package 1 Width	2.8 in (7.2 cm)
Package 1 Length	1.8 in (4.5 cm)
Package 1 Weight	5.08 oz (144.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.7 in (40 cm)
Package 2 Width	11.8 in (30 cm)
Package 2 Length	5.9 in (15 cm)
Package 2 Weight	7.7 lb(US) (3.5 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	768
Package 3 Height	29.5 in (75 cm)
Package 3 Width	31.5 in (80 cm)
Package 3 Length	47.2 in (120 cm)
Package 3 Weight	324.08 lb(US) (147 kg)

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Circularity Profile [End of Life Information](#)

California Proposition 65 **WARNING:** This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov