

Product data sheet

Specifications



EasyLogic PM2130, Power & Energy meter, up to the 31st harmonic, LED display, RS485, class 0.5S

METSEPM2130

Product availability : Stock - Normally stocked in distribution facility

Price* : 866.55 USD

Main

Range	EasyLogic
Product name	EasyLogic PM2100
Device short name	PM2130
Product or Component Type	Power meter

Complementary

Device Application	Sub billing Power monitoring
--------------------	---------------------------------

Power quality analysis	total harmonic distortion up to the 31st harmonic
------------------------	--

Type of measurement	Apparent power min/max, total Active and reactive power min/max, total Current min/max, avg Voltage min/max, avg Frequency min/max, avg Total current harmonic distortion THD (I) per phase Total voltage harmonic distortion THD (U) per phase Power factor min/max, avg Apparent energy total Active and reactive energy total
---------------------	---

Metering type	Peak demand currents Active power P, P1, P2, P3 Demand power P, Q, S Reactive power Q, Q1, Q2, Q3 Apparent power S, S1, S2, S3 Active, reactive, apparent energy (signed, four quadrant) Voltage U, U21, U32, U13, V, V1, V2, V3 Current I, I1, I2, I3 Calculated neutral current Unbalance current Peak demand power PM, QM, SM
---------------	--

Accuracy class	Class 1 reactive energy IEC 62053-24 Class 0.5S active energy IEC 62053-22 Class 5 harmonic distortion (I THD & U THD)
----------------	--

Measurement accuracy	Apparent power +/- 0.5 % Active energy +/- 0.5 % Reactive energy +/- 1 % Active power +/- 0.5 % Voltage +/- 0.5 % Power factor +/- 0.01 Current +/- 0.5 % Frequency +/- 0.05 %
----------------------	---

Measurement current	5...6000 mA
---------------------	-------------

Measurement voltage	35...480 V AC 50/60 Hz between phases
---------------------	---------------------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

20...277 V AC 50/60 Hz between phase and neutral
480...999000 V AC 50/60 Hz with external VT

Frequency measurement range	45...65 Hz
[Us] rated supply voltage	80...277 V AC 45...65 Hz +/- 10 % 100...277 V DC +/- 10 %
Network Frequency	50 Hz 60 Hz
Ride-through time	50 ms 120 V AC typical 50 ms 230 V AC typical 50 ms 125 V DC typical
Line Rated Current	1 A 5 A
Maximum power consumption in VA	8 VA 277 V AC
Maximum power consumption in W	3.3 W power lines (AC) 3.3 W 277 V power lines (DC)
Input impedance	current <= 0.3 mOhm) voltage > 5 MOhm)
Tamperproof of settings	Protected by access code
Display Type	7 segments LED
Display colour	Red
Messages display capacity	3 fields of 4 characters
Display digits	12 - 0.56 in (14.2 mm)
Demand intervals	Configurable from 1 to 60 min
Information displayed	Demand current past value) Demand current present value) Demand power past value) Demand power present value) Voltage Current Frequency Energy consumption Harmonic distortion Power factor Active power Apparent power Reactive power Unbalanced in %
Control type	3 x button
Local signalling	Red LED output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) Green LED module operation and integrated communication
Number of inputs	0
Number of Outputs	0
Communication port protocol	Modbus RTU 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 wires 2500 V
Communication port support	Screw terminal block RS485
Data recording	Power logs Time stamping Energy consumption logs Min/max for 8 parameters
Function Available	Real time clock
Sampling rate	64 samples/cycle
Cybersecurity	Enable/disable communication ports
Communication Service	Remote monitoring
Product certifications	CE IEC 61010-1 CULus UL 61010-1 CULus CSA C22.2 No 61010-1 RCM EAC C-tick
Mounting Mode	Clip-on

Mounting position	Vertical
Mounting support	Framework
Provided equipment	1 x Installation guide
Measurement category	Category III 480 V Category II 480...600 V
Electrical Insulation Class	Class II Double insulation
Flame retardance	V-0 conforming to UL 94
Connections - terminals	Current transformer screw connection bottom) 6 Voltage inputs screw connection top) 4
Material	Polycarbonate
Width	3.78 in (96 mm)
Depth	Total 3.00 in (76.09 mm) Embedded 2.43 in (61.64 mm)
Height	3.78 in (96 mm)
Net Weight	10.58 oz (300 g)
Compatibility code	PM2130

Environment

Service Life	7 year(s)
IP degree of protection	Front IP54 IEC 60529 Body IP30 IEC 60529
Relative humidity	5...95 % 122 °F (50 °C)
Pollution degree	2
Ambient air temperature for operation	14...140 °F (-10...60 °C)
Ambient Air Temperature for Storage	-13...158 °F (-25...70 °C)
Operating altitude	<= 6561.68 ft (2000 m)
Electromagnetic compatibility	Electrostatic discharge IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test IEC 61000-4-3 Electrical fast transient/burst immunity test IEC 61000-4-4 Surge immunity test IEC 61000-4-5 Conducted RF disturbances IEC 61000-4-6 Magnetic field at power frequency IEC 61000-4-8 Voltage dips and interruptions immunity test IEC 61000-4-11 Emission tests FCC Part 15 class A
Overvoltage category	III

Ordering and shipping details

Category	09734-EASYLOGIC METERS AND ACCESSORIES
Discount Schedule	PL1
GTIN	3606480800153
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.53 in (11.5 cm)
Package 1 Width	3.43 in (8.7 cm)

Package 1 Length	4.72 in (12.0 cm)
Package 1 Weight	14.25 oz (404.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	17.00 lb(US) (7.71 kg)
Unit Type of Package 3	P12
Number of Units in Package 3	432
Package 3 Height	31.50 in (80.0 cm)
Package 3 Width	31.50 in (80.0 cm)
Package 3 Length	47.24 in (120.0 cm)
Package 3 Weight	434.56 lb(US) (197.112 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Recommended replacement(s)