

# DATA SHEET



## Three Phase Induction Motor - Squirrel Cage

Customer :					
Product line : Rolled Steel NEMA Premium Efficiency Three-Phase		Product code : 12628412			
		Catalog # : 00156OT3E143T-S			
Frame	: 143/5T	Locked rotor time	: 34s (cold) 19s (hot)		
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 3.70/1.85 A	Cooling method	: IC01 - ODP		
L. R. Amperes	: 31.8/15.9 A	Mounting	: F-1		
LRC	: 8.6x(Code K)	Rotation <sup>1</sup>	: Both (CW and CCW)		
No load current	: 1.62/0.809 A	Noise level <sup>2</sup>	: 62.0 dB(A)		
Rated speed	: 3510 rpm	Starting method	: Direct On Line		
Slip	: 2.50 %	Approx. weight <sup>3</sup>	: 29.4 lb		
Rated torque	: 2.24 ft.lb				
Locked rotor torque	: 210 %				
Breakdown torque	: 330 %				
Insulation class	: F				
Service factor	: 1.15				
Moment of inertia (J)	: 0.0835 sq.ft.lb				
Design	: B				
Output	50%	75%	100%	Foundation loads	
Efficiency (%)	81.5 82.7	84.0 83.6	84.0 82.7	Max. traction : 56 lb	
	81.0	83.3	83.2		
Power Factor	0.73 0.79	0.83 0.88	0.89 0.92	Max. compression : 85 lb	
	0.71	0.83	0.88		
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6205 ZZ	6203 ZZ		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	-	-		
Lubricant amount	:	-	-		
Lubricant type	:	Mobil Polyrex EM			
Notes:					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	27/12/2023			1 / 1	