

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :				
Product line	: Rolled Steel NEMA Premium Efficiency Three-Phase	Product code :	12628413	
		Catalog # :	00118OT3E143T-S	
Frame	: 143/5T	Locked rotor time	: 39s (cold) 22s (hot)	
Output	: 1 HP (0.75 kW)	Temperature rise	: 80 K	
Poles	: 4	Duty cycle	: Cont.(S1)	
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C	
Rated voltage	: 230/460 V	Altitude	: 1000 m.a.s.l.	
Rated current	: 3.02/1.51 A	Cooling method	: IC01 - ODP	
L. R. Amperes	: 24.2/12.1 A	Mounting	: F-1	
LRC	: 8.0x(Code L)	Rotation ¹	: Both (CW and CCW)	
No load current	: 1.92/0.958 A	Noise level ²	: 52.0 dB(A)	
Rated speed	: 1760 rpm	Starting method	: Direct On Line	
Slip	: 2.22 %	Approx. weight ³	: 34.9 lb	
Rated torque	: 2.98 ft.lb			
Locked rotor torque	: 290 %			
Breakdown torque	: 360 %			
Insulation class	: F			
Service factor	: 1.15			
Moment of inertia (J)	: 0.1101 sq.ft.lb			
Design	: B			
Output	25% 50% 75% 100%	Foundation loads		
Efficiency (%)	79.9 82.2 81.5 81.9 84.0 83.4 85.5 82.6	Max. traction	: 86 lb	
	79.4 80.1 82.9 83.2			
Power Factor	0.29 0.34 0.51 0.59 0.65 0.73 0.73 0.80	Max. compression	: 121 lb	
	0.29 0.52 0.66 0.75			
		Drive end	Non drive end	
Bearing type	:	6205 ZZ	6203 ZZ	
Sealing	:	Without Bearing Seal	Without Bearing Seal	
Lubrication interval	:	-	-	
Lubricant amount	:	-	-	
Lubricant type	:	Mobil Polyrex EM		
Notes				
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.		These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	31/07/2023		1 / 1	