DATA SHEET

Three Phase Induction Motor - Squirrel Cage

:



Customer

| Product line | | : Rolled Steel NEMA Premium Efficiency Three-Phase | | n Product code : | 12674853 | |
|--|---|--|---------------------|------------------------------------|-------------------------------|----------------|
| | | | 111100-111050 | Catalog # : | 01018OT3H | 1215T-S |
| Frame | | : 213/5T | | Locked rotor time | : 25s (cold) |) 14s (hot) |
| Output | | : 10 HP (7 | .5 kW) | Temperature rise | : 80 K | |
| Poles | | : 4 | | Duty cycle | : Cont.(S1) | |
| Frequency | | : 60 Hz | | Ambient temperature | : -20°C to + | |
| Rated voltage | | : 575 V | | Altitude | : 1000 m.a. | |
| Rated current | | : 9.92 A | | Cooling method | : IC01 - OD |)P |
| L. R. Amperes | | : 69.4 A | | Mounting | : F-1 | |
| LRC | | : 7.0x(Coc | le H) | Rotation ¹ | : Both (CW and CCW) | |
| No load current | | : 4.79 A | | Noise level ² | : 59.0 dB(A | |
| Rated speed | | : 1770 rpm | | Starting method | : Direct On | Line |
| Slip Batad targua | | : 1.67 % | | Approx. weight ³ | : 120 lb | |
| Rated torque | | : 29.7 ft.lb | | | | |
| Locked rotor torque Breakdown torque | | : 250 % : 350 % | | | | |
| Insulation class | le | : 550 % : F | | | | |
| Service factor | | : 1.15 | | | | |
| Moment of inertia | a (1) | : 1.30 sq.f | t lb | | | |
| Design | a (J) | : 1.50 Sq.1 : B | | | | |
| Output | 50% | 75% | 100% | Foundation loads | | |
| Efficiency (%) | 90.2 | 91.0 | 91.7 | Max. traction | : 526 lb | |
| Power Factor | 0.64 | 0.77 | 0.83 | Max. compression | : 646 lb | |
| | | | | | | |
| Bearing type | | : <u>Drive end</u> : 6208 ZZ | | Non drive end 6206 ZZ | | |
| Bearing type Sealing | | · \\/it | hout Bearing Seal | 6206 ZZ Without Bearing Seal | | |
| Lubrication interv | /al | | - | - | Jeal | |
| Lubricant amoun | | : | _ | | | |
| Lubricant type | i. | | Mot | oil Polyrex EM | | |
| | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| Notes | | | | | | |
| This revision repla | | ncel the previ | ious one, which | These are average values | | |
| Notes This revision repl must be eliminate | ed. | | ious one, which | power supply, subject to the | | |
| This revision repl must be eliminate (1) Looking the m | ed. otor from th | e shaft end. | | | | |
| This revision repl must be eliminate (1) Looking the m (2) Measured at 1 | ed. lotor from th Im and with | e shaft end. tolerance of - | +3dB(A). | power supply, subject to the | | |
| This revision repl must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v | ed. lotor from th Im and with weight subje | e shaft end. tolerance of - | +3dB(A). | power supply, subject to the | | |
| This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of - | +3dB(A). | power supply, subject to the | | |
| This revision repla nust be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v nanufacturing pro | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of - | +3dB(A). | power supply, subject to the | | |
| This revision replanust be eliminate 1) Looking the m 2) Measured at 1 3) Approximate v nanufacturing pro | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of + ect to changes | +3dB(A). | power supply, subject to the | | |
| This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of + ect to changes | ⊦3dB(A). ∋ after | power supply, subject to the MG-1. | e tolerances stipu | lated in NEMA |
| This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of + ect to changes | ⊦3dB(A). ∋ after | power supply, subject to the MG-1. | e tolerances stipu | lated in NEMA |
| This revision replanust be eliminate 1) Looking the m 2) Measured at 1 3) Approximate v nanufacturing pro 4) At 100% of ful Rev. | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of + ect to changes | ⊦3dB(A). ∋ after | power supply, subject to the MG-1. | e tolerances stipu | lated in NEMA |
| This revision repla must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful Rev. | ed. lotor from th Im and with weight subje ocess. | e shaft end. tolerance of + ect to changes Change | ⊦3dB(A). ∋ after | power supply, subject to the MG-1. | e tolerances stipu Checked | Ilated in NEMA |