DATA SHEET

:

Three Phase Induction Motor - Squirrel Cage



Customer

Product line		ed Steel NEW	IA Premium Efficier	rcy Product code :	12682570	
	Thee	1 11030		Catalog # :	00156OT3H	1143TC-S
Frame Output Poles Frequency Rated voltage Rated current L. R. Amperes LRC No load current Rated speed Slip Rated torque Locked rotor toro Breakdown torqu Insulation class Service factor Moment of inertia Design	ue	: 143/5TC : 1.5 HP (: 2 : 60 Hz : 575 V : 1.48 A : 12.7 A : 8.6x(Coo : 0.647 A : 3510 rpr : 2.50 % : 2.24 ft.lb : 210 % : 330 % : F : 1.15 : 0.0835 s : B	1.1 kW) de K) n	Locked rotor time Temperature rise Duty cycle Ambient temperature Altitude Cooling method Mounting Rotation ¹ Noise level ² Starting method Approx. weight ³	: 34s (cold) : 80 K : Cont.(S1) : -20°C to + : 1000 m.a. : IC01 - OD : F-1 : Both (CW : 62.0 dB(A : Direct On : 29.8 lb	-40°C .s.l.)P and CCW)
Output	50%	75%	100%	Foundation loads		
Efficiency (%)	81.5	84.0	84.0	Max. traction	: 49 lb	
Power Factor	0.73	0.83	0.89	Max. compression	: 79 lb	
Bearing type Sealing		: • \\/ii	6205 ZZ hout Bearing Seal	6203 ZZ Without Bearin		
Lubrication inter Lubricant amoun Lubricant type Notes:			-	- bil Polyrex EM		
Lubrication inter- Lubricant amour Lubricant type Notes: This revision repl must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful	laces and ca ed. notor from the 1m and with weight subje ocess.	ncel the prev e shaft end. tolerance of ct to changes	ious one, which +3dB(A).	- bil Polyrex EM	s based on tests wi	lated in NEMA
Lubrication inter- Lubricant amour Lubricant type Notes: This revision repl must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro-	laces and ca ed. notor from the 1m and with weight subje ocess.	ncel the prev e shaft end. tolerance of ct to changes	ious one, which	- bil Polyrex EM	s based on tests wi	
Lubrication inter- Lubricant amoun Lubricant type Notes: This revision repl must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful Rev.	laces and ca ed. notor from the 1m and with weight subje ocess.	ncel the prev e shaft end. tolerance of ct to changes	ious one, which +3dB(A).	- bil Polyrex EM	s based on tests wi	lated in NEMA
Lubrication inter- Lubricant amour Lubricant type Notes: This revision repl must be eliminate (1) Looking the m (2) Measured at 1 (3) Approximate v manufacturing pro (4) At 100% of ful	laces and ca ed. notor from the 1m and with weight subje ocess.	ncel the prev e shaft end. tolerance of ct to changes	ious one, which +3dB(A).	- bil Polyrex EM	s based on tests wi	lated in NEMA

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

Subject to change without notice