

# DATA SHEET



## Single Phase Induction Motor - Squirrel Cage

Customer :																						
Product line : Rolled Steel Single-Phase			Product code : 12882454																			
			Catalog # : 00218OT1B56-S																			
Frame : 56H Output : 2 HP (1.5 kW) Poles : 4 Frequency : 60 Hz Rated voltage : 115/208-230 V Rated current : 17.7/9.50-8.87 A L. R. Amperes : 115/61.7-57.7 A LRC : 6.5x(Code H) No load current : 6.20/2.67-3.10 A Rated speed : 1730 rpm Slip : 3.89 % Rated torque : 6.07 ft.lb Locked rotor torque : 290 % Breakdown torque : 225 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.1614 sq.ft.lb Design : A			Locked rotor time : 32s (cold) 18s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Cooling method : IC01 - ODP Mounting : F-1 Rotation <sup>1</sup> : Both (CW and CCW) Noise level <sup>2</sup> : 52.0 dB(A) Starting method : Direct On Line Approx. weight <sup>3</sup> : 49.6 lb																			
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td>Output</td> <td>25%</td> <td>50%</td> <td>75%</td> <td>100%</td> </tr> <tr> <td>Efficiency (%)</td> <td>82.2</td> <td>83.0</td> <td>84.0</td> <td>84.5</td> </tr> <tr> <td>Power Factor</td> <td>0.49</td> <td>0.75</td> <td>0.83</td> <td>0.87</td> </tr> </table>			Output	25%	50%	75%	100%	Efficiency (%)	82.2	83.0	84.0	84.5	Power Factor	0.49	0.75	0.83	0.87	Foundation loads Max. traction : 109 lb Max. compression : 159 lb				
Output	25%	50%	75%	100%																		
Efficiency (%)	82.2	83.0	84.0	84.5																		
Power Factor	0.49	0.75	0.83	0.87																		
<table style="width:100%; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;"><u>Drive end</u></td> <td style="text-align: center;"><u>Non drive end</u></td> </tr> <tr> <td>Bearing type :</td> <td style="text-align: center;">6204 ZZ</td> <td style="text-align: center;">6202 ZZ</td> </tr> <tr> <td>Sealing :</td> <td style="text-align: center;">Without Bearing Seal</td> <td style="text-align: center;">Without Bearing Seal</td> </tr> <tr> <td>Lubrication interval :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Lubricant amount :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Lubricant type :</td> <td colspan="2" style="text-align: center;">Mobil Polyrex EM</td> </tr> </table>						<u>Drive end</u>	<u>Non drive end</u>	Bearing type :	6204 ZZ	6202 ZZ	Sealing :	Without Bearing Seal	Without Bearing Seal	Lubrication interval :	-	-	Lubricant amount :	-	-	Lubricant type :	Mobil Polyrex EM	
	<u>Drive end</u>	<u>Non drive end</u>																				
Bearing type :	6204 ZZ	6202 ZZ																				
Sealing :	Without Bearing Seal	Without Bearing Seal																				
Lubrication interval :	-	-																				
Lubricant amount :	-	-																				
Lubricant type :	Mobil Polyrex EM																					
Notes																						
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																			
Rev.	Changes Summary		Performed	Checked	Date																	
Performed by				Page      Revision 1 / 1																		
Checked by																						
Date		31/07/2023																				