

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer : _____

Product line : ROLLED STEEL
 Product code : 12882457
 Catalog # : 00158OT1B56-S

Frame	: 56H	Locked rotor time	: 39s (cold) 22s (hot)
Output	: 1.5 HP (1.1 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.
Rated current	: 13.0/7.52-6.49 A	Cooling method	: IC01 - ODP
L. R. Amperes	: 105/60.9-52.6 A	Mounting	: F-1
LRC	: 8.1x(Code K)	Rotation ¹	: Both (CW and CCW)
No load current	: 4.60/1.98-2.30 A	Noise level ²	: 52.0 dB(A)
Rated speed	: 1740 rpm	Starting method	: Direct On Line
Slip	: 3.33 %	Approx. weight ³	: 45.2 lb
Rated torque	: 4.53 ft.lb		
Locked rotor torque	: 320 %		
Breakdown torque	: 229 %		
Insulation class	: F		
Service factor	: 1.15		
Moment of inertia (J)	: 0.1362 sq.ft.lb		
Design	: L		

Output	25%	50%	75%	100%	Foundation loads	
Efficiency (%)	79.4	80.5	83.0	83.8	Max. traction	: 79 lb
Power Factor	0.52	0.78	0.85	0.88	Max. compression	: 125 lb

	Drive end	Non drive end
Bearing type	: 6204 ZZ	: 6202 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.
 (1) Looking the motor from the shaft end.
 (2) Measured at 1m and with tolerance of +3dB(A).
 (3) Approximate weight subject to changes after manufacturing process.
 (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	24/04/2023		1 / 1	