

# DATA SHEET



## Single Phase Induction Motor - Squirrel Cage

Customer :					
Product line : Rolled Steel Single-Phase		Product code : 13107364			
		Catalog # : 00336OT1B56CFL-S			
Frame : 56C Output : 3 HP (2.2 kW) Poles : 2 Frequency : 60 Hz Rated voltage : 115/208-230 V Rated current : 24.4/13.5-12.2 A L. R. Amperes : 200/111-100 A LRC : 8.2x(Code J) No load current : 7.80/3.36-3.90 A Rated speed : 3500 rpm Slip : 2.78 % Rated torque : 4.50 ft.lb Locked rotor torque : 220 % Breakdown torque : 280 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.0944 sq.ft.lb Design : L		Locked rotor time : 10s (cold) 6s (hot) Temperature rise : 80 K Duty cycle : Cont.(S1) Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Cooling method : IC01 - ODP Mounting : F-1 Rotation <sup>1</sup> : Both (CW and CCW) Noise level <sup>2</sup> : 58.0 dB(A) Starting method : Direct On Line Approx. weight <sup>3</sup> : 45.8 lb			
Output	25%	50%	75%	100%	
Efficiency (%)	73.2	76.0	81.0	84.1	
Power Factor	0.61	0.87	0.92	0.93	
Foundation loads					
Max. traction : 101 lb					
Max. compression : 146 lb					
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6204 ZZ	6202 ZZ		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	-	-		
Lubricant amount	:	-	-		
Lubricant type	:	Mobil Polyrex EM			
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	31/07/2023			1 / 1	