

DATA SHEET



Three Phase Induction Motor - Squirrel Cage

Customer :																			
Product line	: Multimounting High Efficiency Three-Phase																		
Product code :	13982682																		
Catalog # :	.1818EP3EALR63FF-W22																		
Frame : 63 Output : 0.25 HP (0.18 kW) Poles : 4 Frequency : 60 Hz Rated voltage : 230/460 V Rated current : 1.02/0.512 A L. R. Amperes : 4.71/2.36 A LRC : 4.6 No load current : 0.940/0.470 A Rated speed : 1710 rpm Slip : 5.00 % Rated torque : 0.768 ft.lb Locked rotor torque : 280 % Breakdown torque : 290 % Insulation class : F Service factor : 1.15 Moment of inertia (J) : 0.0133 sq.ft.lb Design : N	Locked rotor time : 34s (cold) 19s (hot) Temperature rise : 80 K Duty cycle : S1 Ambient temperature : -20°C to +40°C Altitude : 1000 m.a.s.l. Protection degree : IP55 Cooling method : IC411 - TEFC Mounting : B5T Rotation ¹ : Both (CW and CCW) Noise level ² : 48.0 dB(A) Starting method : Direct On Line Approx. weight ³ : 15.4 lb																		
Output	25% 50% 75% 100%																		
Efficiency (%)	61.0 63.0 67.0 69.0																		
Power Factor	0.22 0.42 0.54 0.64																		
Foundation loads																			
Max. traction : 22 lb																			
Max. compression : 38 lb																			
	<table border="0"> <tr> <td></td> <td style="text-align: center;"><u>Drive end</u></td> <td style="text-align: center;"><u>Non drive end</u></td> </tr> <tr> <td>Bearing type :</td> <td style="text-align: center;">6201 ZZ</td> <td style="text-align: center;">6201 ZZ</td> </tr> <tr> <td>Sealing :</td> <td style="text-align: center;">Oil Seal</td> <td style="text-align: center;">Oil Seal</td> </tr> <tr> <td>Lubrication interval :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Lubricant amount :</td> <td style="text-align: center;">-</td> <td style="text-align: center;">-</td> </tr> <tr> <td>Lubricant type :</td> <td colspan="2" style="text-align: center;">Mobil Polyrex EM</td> </tr> </table>		<u>Drive end</u>	<u>Non drive end</u>	Bearing type :	6201 ZZ	6201 ZZ	Sealing :	Oil Seal	Oil Seal	Lubrication interval :	-	-	Lubricant amount :	-	-	Lubricant type :	Mobil Polyrex EM	
	<u>Drive end</u>	<u>Non drive end</u>																	
Bearing type :	6201 ZZ	6201 ZZ																	
Sealing :	Oil Seal	Oil Seal																	
Lubrication interval :	-	-																	
Lubricant amount :	-	-																	
Lubricant type :	Mobil Polyrex EM																		
Notes																			
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.																			
These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.																			
Rev.	Changes Summary	Performed	Checked	Date															
Performed by																			
Checked by			Page	Revision															
Date	12/01/2022		1 / 1																