

DATA SHEET

Single Phase Induction Motor - Squirrel Cage



Customer :

Product line : Rolled Steel Single-Phase

Product code : 14360135

Catalog # : .2536OT1BW56-S

Frame : W56
Output : 0.25 HP (0.18 kW)
Poles : 2
Frequency : 60 Hz
Rated voltage : 115/208-230 V
Rated current : 2.50/1.38-1.25 A
L. R. Amperes : 22.0/12.1-11.0 A
LRC : 8.8x(Code M)
No load current : 1.00/0.431-0.500 A
Rated speed : 3510 rpm
Slip : 2.50 %
Rated torque : 0.052 kgfm
Locked rotor torque : 280 %
Breakdown torque : 310 %
Insulation class : F
Service factor : 1.35
Moment of inertia (J) : 0.0009 kgm²
Design : N

Locked rotor time : 32s (cold) 18s (hot)
Temperature rise : 80 K
Duty cycle : Cont.(S1)
Ambient temperature : -20°C to +40°C
Altitude : 1000 m.a.s.l.
Cooling method : IC01 - ODP
Mounting : F-1
Rotation¹ : Both (CW and CCW)
Noise level² : 56.0 dB(A)
Starting method : Direct On Line
Approx. weight³ : 7.8 kg

Output	50%	75%	100%
Efficiency (%)	50.0	59.0	66.6
Power Factor	0.91	0.93	0.94

Foundation loads
Max. traction : 1 kgf
Max. compression : 9 kgf

	Drive end	Non drive end
Bearing type	: 6203 ZZ	: 6202 ZZ
Sealing	: Without Bearing Seal	: Without Bearing Seal
Lubrication interval	: -	: -
Lubricant amount	: -	: -
Lubricant type	: Mobil Polyrex EM	

Notes

This revision replaces and cancel the previous one, which must be eliminated.

- (1) Looking the motor from the shaft end.
- (2) Measured at 1m and with tolerance of +3dB(A).
- (3) Approximate weight subject to changes after manufacturing process.
- (4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	12/01/2022		1 / 1	