

DATA SHEET



Single Phase Induction Motor - Squirrel Cage

Customer :					
Product line : ROLLED STEEL		Product code : 14419290 Catalog # : .5036OT1B48CH-S			
Frame	: 48	Locked rotor time	: 16s (cold) 9s (hot)		
Output	: 0.5 HP (0.37 kW)	Temperature rise	: 80 K		
Poles	: 2	Duty cycle	: Cont.(S1)		
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C		
Rated voltage	: 115/208-230 V	Altitude	: 1000 m.a.s.l.		
Rated current	: 4.80/2.65-2.40 A	Cooling method	: IC01 - ODP		
L. R. Amperes	: 42.2/23.3-21.1 A	Mounting	: F-1		
LRC	: 8.8x(Code L)	Rotation ¹	: Both (CW and CCW)		
No load current	: 1.60/0.690-0.800 A	Noise level ²	: 56.0 dB(A)		
Rated speed	: 3510 rpm	Starting method	: Direct On Line		
Slip	: 2.50 %	Approx. weight ³	: 8.8 kg		
Rated torque	: 0.103 kgfm				
Locked rotor torque	: 270 %				
Breakdown torque	: 300 %				
Insulation class	: F				
Service factor	: 1.25				
Moment of inertia (J)	: 0.0011 kgm ²				
Design	: N				
Output	25%	50%	75%	100%	
Efficiency (%)	56.6	60.0	68.0	72.4	
Power Factor	0.64	0.90	0.93	0.94	
Foundation loads		Max. traction : 7 kgf Max. compression : 15 kgf			
		<u>Drive end</u>	<u>Non drive end</u>		
Bearing type	:	6203 ZZ	6202 ZZ		
Sealing	:	Without Bearing Seal	Without Bearing Seal		
Lubrication interval	:	-	-		
Lubricant amount	:	-	-		
Lubricant type	:	Mobil Polyrex EM			
Notes					
This revision replaces and cancel the previous one, which must be eliminated. (1) Looking the motor from the shaft end. (2) Measured at 1m and with tolerance of +3dB(A). (3) Approximate weight subject to changes after manufacturing process. (4) At 100% of full load.			These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.		
Rev.	Changes Summary		Performed	Checked	Date
Performed by					
Checked by				Page	Revision
Date	26/03/2023			1 / 1	